



S N O W P L O W

BOSS EXT

Features:

- SmartLight™ 3 100% L.E.D. lighting system with up to 2x the light output and featuring Ice Shield Technology™ to prevent ice build-up.
- Expandable Fully Hydraulic Wings — Expand your plow potential when you get to the larger, more widespread job sites by extending the wings of the EXT. At the touch of a button, the 8-foot blade expands to 10 feet, quickly and efficiently clearing more snow.
- Standard RT3 Undercarriage — The EXT uses the BOSS universal undercarriage system, which means you can quickly and easily swap the EXT between any truck in your fleet — from EXT, to DXT, to Straight.
- Full Trip Design — When obstacles are encountered, the entire blade trips forward to protect the truck and plow from damage.
- Urethane Edges — The EXT wings feature urethane edges to protect parking lots. Urethane's material composition is a type of durable, heavy-duty, flexible plastic. The nature of the urethane material allows it to mold to the ground surface. Because of this, it creates a squeegee effect and performance is maximized when plowing fresh snow or slushy conditions.
- Curb Guards standard
- Blade Leveling Adjustment — Adjust the angle of the moldboard forward or backward for improved scraping ability.
- Simple design — Designed with the simplicity and ingenuity that you expect from BOSS, this snowplow is best in class. The EXT design makes it easy to access the hydraulics, making it a very serviceable snowplow.
- Chainless Hydraulic Cylinder Lifting System virtually eliminates snowplow "bounce" associated with transporting a plow.
- Enclosed High-Performance Hydraulic System delivers speed and reliability and is protected from the elements to prevent corrosion and hydraulic freeze-up.
- SmartShield — Only BOSS treats every plow with our exclusive SmartShield finish to deliver durable corrosion protection and a long-lasting, high-gloss shine.
- SmartHitch® 2 — Designed to be simple and easy to use.
- Cutting Edge standard
- Built-in locations for plow shoes (plow shoes are an optional accessory)
- Reinforced Moldboard Diagonal cross-bracing and formed bottom channel increase blade rigidity.
- Adjustable Trip Springs
- 2-Year Warranty covers both parts and labor for two full years.

EXT Specifications	
Blade Width Retracted	96" (244 cm)
Blade Width Extended	120" (305 cm)
Plowing Width @ 30-degree angle	83" (211 cm)-IN 103" (262 cm)- OUT
Blade Height	30" (76 cm)
Blade Thickness	11-ga steel
Cutting Edge	1/2" x 6" (1.27 cm x 15 cm)
Reinforcement Ribs	9 vertical
Plow Shoes	Optional
Trip Springs	4
Angle Cylinders	1-1/2" x 10" (4 cm x 25 cm)
Wing Cylinders	1-1/2" x 1-1/8" x 12-3/4" (4 cm x 3 cm x 32 cm)
Lift Cylinder	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)
Shock Absorber	1
Attachment System	RT3
Plowing Weight	970 lbs.
Plow Lights	SL3 L.E.D. with Ice Shield Technology