



S N O W P L O W

BOSS FORGE Specifications

Feature	Auger	Pintle
Hopper Capacity	2 cubic yards (1.53 cubic m)	2 cubic yards (1.53 cubic m)
Hopper Length	69" (175.26 cm)	69" (175.26 cm)
Hopper Height	38" (96.5 cm)	38" (96.5 cm)
Hopper Width	48" (122 cm)	48" (122 cm)
Spreader Overall Length	98" (249 cm)	98" (249 cm)
Spreader Weight (Empty)	650 lb (295 kg)	700 lb (318 kg)
Hopper Construction	14ga Stainless Steel	14ga Stainless Steel
Spreading Width	2 ft-40 ft (0.6 m - 12.2 m)	2 ft-40 ft (0.6 m - 12.2 m)
Max Feed Rate	2.3 cu ft (0.06 cu m) per min	4.0 cu ft (0.11 cu m) per min
Work Lighting	Optional	Optional
Cover	Optional Tarp	Optional Tarp
Top Screen	Standard	Standard
Gearbox and Ratio	Planetary Worm Gearbox 91:1	Planetary Worm Gearbox 137:1
Motor	1/2 HP Motor	1/2 HP Motor
Trough	11ga Stainless Steel	11ga Stainless Steel
Control	Dual-Variable Speed Controller (Non-LCD Display)	Dual-Variable Speed Controller (Non-LCD Display)
Vibrators	1 Standard	Optional
Inverted V Baffle	Standard	Optional
Material Conveying Method	6" (15 cm) OD X 9" (23 cm) Pitch Full Length Auger	14" (36 cm) Wide Pintle Chain
LED CHMSL	Standard	Standard
Adjustable Deflector	Standard	Standard
Spinner Assembly	Easily Removable/Swing Out	Easily Removable/Swing Out
Hopper Tie-Down Kit	Standard	Standard
Spinner	14.5" (36.8 cm) Diameter Urethane Spinner	14.5" (36.8 cm) Diameter Urethane Spinner
Spinner Gearmotor	1/8 HP Gearmotor (Located Above Spinner)	1/8 HP Gearmotor (Located Above Spinner)
Minimum Bed Length	6' 6" (168 cm)	6' 6" (168 cm)
Minimum GVWR	10,000 lb (4,535 kg)	10,000 lb (4,535 kg)