



S N O W P L O W

BOSS VBX 6500

Standard Features:

- **Corrosion-Resistant Poly Hopper** is built to outlast the elements and has 1.5 cubic yards of spreading capacity.
- **Pintle Chain or Auger Feed System** is available, allowing you to choose the best system for your needs.
- **Remote Light Switch** turns spreader lights on and off from inside the truck cab and at the rear of the spreader for ease of operation and safety.
- **Standard Twin Vibrators** prevent material bridging for ease of operation. (Standard on auger and optional on pintle.)
- **Two-Year Limited Warranty** protects against material defects for peace of mind.

Specs On Next Page

VBX 6500 Specifications

	Auger	Pintle
Hopper Capacity	1.5 yards	1.5 yards
Hopper Length	78" (198.1 cm)	78" (198.1 cm)
Hopper Overall Length	93-1/2" (237.5 cm)	93-1/2" (237.5 cm)
Hopper Height	38-3/16" (97 cm)	38-3/16" (97 cm)
Hopper Width	48-1/4" (122.6 cm)	48-1/4" (122.6 cm)
Full Unit Weight	550 lb (250 kg)	600 lb (272 kg)
Hopper Construction	3/16" (0.5 cm) Double Wall Polyethylene Hopper	3/16" (0.5 cm) Double Wall Polyethylene Hopper
Spread Width	2 ft - 40 ft (0.6 m - 12 m) Dry, free-flowing material	2 ft - 40 ft (0.6 m - 12 m) Dry, free-flowing material
Max Feed Rate	2.3 cu ft (0.06 cu m) per minute	4 cu ft (0.11 cu m) per minute
Lighting	Dual 55 watt halogen variable output worklights	Dual 55 watt halogen variable output worklights
Cover	VCP Tarp w/ integral tie-downs	VCP Tarp w/ integral tie-downs
Top Screen	Standard	Standard
Gearbox	Planetary Gearbox	Planetary Gearbox
Motor	3/4 HP SS Feed Motor	3/4 HP SS Feed Motor
Trough	304 Stainless Steel	304 Stainless Steel
Cab Controller	LCD Display Controller	LCD Display Controller
Dual Variable Speed Control	Standard	Standard
Single Vibrator	N/A	N/A
Dual Variable Speed Vibrators	Standard	Standard
Single Vibrator	N/A	N/A
Inverted V Baffle	Standard	Optional
Feed System	6" OD x 9" (15 cm x 23 cm) pitch full length Auger	14" (36 cm) wide Pintle Chain
LED CHSML	Standard	Standard
Adjustable Deflector	Standard	Standard
Spinner Assembly	Easily removable and height adjustable	Easily removable and height adjustable
Hopper Tie-Down Kit	Standard	Standard
Spinner	14.5" (36.8 cm) Diameter Urethane Spinner	14.5" (36.8 cm) Diameter Urethane Spinner
Spinner Gearmotor	1/8 HP Spinner Gearmotor (Located above spinner)	1/8 HP Spinner Gearmotor (Located above spinner)
Minimum Bed Length	5'6" (167.6 cm)	5'6" (167.6 cm)
Minimum GVWR	9,000 lb Gross Vehicle Weight Required	9,000 lb Gross Vehicle Weight Required